## plantronics


## **Electronic Hook Switch for NEC**<sup>®</sup>




EHS Setup Use the EHS setup below to automatically answer a desk phone call by pressing a button on your Savi 700 Series, CS500/CS500 XD Series or Voyager Legend CS headset or MDA200.


NEC models: DSX 34B BL, DSX 34B FDX, DTR series, DTH series, DTL series, DT 330, DT 730 and DT 750

Setup



Configuration





Install the ringer detect device on the phone over the speaker, under the handset. This is then plugged into the socket mounted midway along the audio cable. Supports only DT700/300 Series. Please contact NEC for more information.

 $\Delta$  Note: Disconnect the phone from the network cable prior to installing the EHS cable. Insert cable "A" per diagram, and install the plastic flap included with the APN-91 cable, per the diagram prior to reconnecting the network connection. Please wait 20-30 seconds after all connections are made before pressing the headset button to make a call. Please contact NEC for more information.

\*The NEC DT Series phones come in 2 versions, the std SIP (used with NEC product SIP@NET and 3C) and the i-SIP/N-SIP versions which are used with the SV8100, SV8300 and SV8500. The APN-91 only works with the i-SIP/N-SIP versions of the DT700 terminals.

For phone set-up, please refer to your specific phone manufacturers instructions.