

# MAXAttach™

## Expandable Tabletop Conference Phones

The industry's first fully expandable tabletop conference phones. MAXAttach comes with two complete phone units and provides premium, full-duplex audio in medium sized rooms. It also features the ability to link up to two additional phone units for unrivaled microphone and loudspeaker coverage in larger rooms.

**ClearOne.**



UNRIVALED AUDIO  
QUALITY, FLEXIBILITY  
AND AFFORDABILITY

### MAXATTACH APPLICATIONS

- Executive Office
- Medium Conference Room
- Large Conference Room
- Training Room
- Separate Rooms

### MAXATTACH ADVANTAGES

#### Superior Audio Performance

- + Distributed Echo Cancellation® effectively eliminates echo
- + Noise cancellation removes background noises from fans or HVAC systems
- + Full-duplex sound enables participants to speak and listen at the same time without cutting in and out
- + Automatic level controls keep participants' audio balanced and consistent
- + First-mic priority eliminates hollow "tunnel" sound by activating only the microphone closest to the person speaking
- + Three microphones in each phone unit provide 360° audio pickup

#### Expandability

##### MAXAttach

- + Comes with two phone units and a single base unit for medium conference rooms; also available in 3-phone and 4-phone kits
- + Link up to four complete phones, not just microphones, for expanded coverage with MAX EX Expansion Kits
- + Divide MAXAttach into multiple phone systems for use in separate rooms with MAX EX Expansion Base

##### MAX EX Expansion Kit

- + Includes phone and connecting cable to expand MAXAttach room coverage (base not included)

##### MAX EX Expansion Base


- + Used to divide MAXAttach into multiple phone systems for use in separate rooms to provide unrivaled flexibility and affordability

#### Ease of Use & Control


- + Simply plug base unit into power and phone line, connect the phones, then dial and talk
- + Features user-friendly telephone style controls
- + Speed dial stores 10 frequently dialed numbers
- + Recording output on base unit connects to a recording device to capture both sides of the conversation
- + Linked MAX phones can be operated using the dial pad of any phone – dialing, mute, volume controls, etc.

## → ROOM APPLICATIONS


**MAXAttach™**




**MAXAttach + 1 Exp. Kit**



**MAXAttach + 2 Exp. Kits**



**MAX EX Expansion Base**



**MAX EX Expansion Kit**

Use with any MAX Phone to expand coverage up to 4 total units.

Enables MAXAttach and MAX EX Expansion Kits to be used in separate rooms. Includes power supply and 25' cable.

## → SPECIFICATIONS

**Echo Cancellation**

Tail time: 60 ms x 3

**Noise Cancellation**

Dynamic noise cancellation

**Telephone Connection**

Analog PBX or PSTN line  
RJ-11C, -12 dBm nominal

**Keypad**

Alphanumeric standard keypad

**Loudspeaker**

Volume: 90dBspl A weighted @ 1 ft  
Bandwidth: 200 Hz–3.3 kHz

**Record Output**

Connector: 2.5 mm mono audio jack  
Impedance: < 1000 ohms  
Bandwidth: 200 Hz–3.3 kHz  
Dynamic range: 60 dB  
THD < .01%

**Certifications**

FCC part 15 Class A  
FCC part 68  
UL Certified

**Power**

Base unit:  
Auto-adjusting power module;  
100-240 VAC; 50/60 Hz

**Environmental**

Operating temperature: 32–122° F  
(0–50° C)  
Storage temperature: 41–158° F  
(5–70° C)  
Operating humidity: 15 to 80%  
Storage humidity: 10 to 90%

**Dimensions (W x D x H)**

Phone unit: 10.5" x 10.5" x 3"  
(26.7 cm x 26.7 cm x 7.6 cm)  
Base unit: 4.25" x 5.5" x 2.5"  
(10.8 cm x 14 cm x 6.4 cm)

**Weight**

Phone unit: 2.7 lb (1.2 kg)  
Base unit: .6 lb (0.27 kg)  
Shipping: 10 lb (4.5 kg)

**PART NUMBERS**

**MAXAttach\***

- 910-158-055 (North America)
  - 910-158-057 (Europe)
  - 910-158-058 (United Kingdom)
  - 910-158-056 (Japan)
  - 910-158-059 (Australia/New Zealand)
  - 910-158-060 (South Africa)
  - 910-158-061 (South Korea)
  - 910-158-062 (China)
- \* For MaxAttach plus 1, add -01 to part number; for MaxAttach plus 2, add -02 to part number.

Includes:

- MAX phone units (2)
- MAX base unit (1)
- 12' Cat. 5 cable (1)
- 25' Cat. 5 cable (1)
- Telephone cable
- Documentation CD
- Quick start guide

**MAX EX Expansion Kit**

910-158-050 (All countries)

Includes:

- MAX phone unit (1)
- 12' Cat. 5 cable (1)
- Documentation CD
- Quick start guide

**MAX EX Expansion Base**

910-158-048 (North America, Brazil, Taiwan)  
910-158-049 (All other countries)

Includes:

- MAX base unit (1)
- 25' Cat. 5 cable (1)
- Telephone cable
- Documentation CD
- Quick start guide



## → CLEARONE LOCATIONS

**Headquarters:**  
**Salt Lake City, UT USA**  
1825 Research Way  
Salt Lake City, UT 84119  
**Tel:** 801-975-7200;  
800-945-7730  
**Fax:** 801-977-0087  
sales@clearone.com

**Champlin, MN USA**  
**Tel:** 801-942-3776  
sales@clearone.com

**Latin America Offices**  
**Tel:** 801-974-3621  
global@clearone.com

**London, UK**  
**Tel:** 801-974-3792  
global@clearone.com

**Hong Kong**  
**Tel:** 801-303-3441  
global@clearone.com

**Singapore**  
**Tel:** 801-303-3495  
global@clearone.com